



NOTES:

- 1. HSL = HIGH SIDE TRANSITION LENGTH(SEE M/E 107.9.0)
- 2. TOLERANCE FOR CONSTRUCTION IS +/- 0.5%
- 3. DETECTABLE WARNINGS SHALL CONSIST OF RAISED TRUNCATED DOMES WITH A DIAMETER OF NOMINAL 0.9", A HEIGHT OF NOMINAL 0.2" AND A CENTER-TO-CENTER SPACING OF NOMINAL 2.35" AND SHALL BE BRICK RED.
- 4. ALL WHEEL-CHAIR RAMPS SHALL COMPLY WITH JULY 1, 1994 ADA STANDARDS FOR ACCESSIBLE DESIGN OR MOST RECENT EDITION, MASS HIGHWAY ENGINEERING DIRECTIVE M/E 107.2.1R AND M/E 107.6.5R, AND SECTION 701 OF THE 1995 MASS HIGHWAY STANDARD SPECIFICATIONS FOR HIGHWAYS AND BRIDGES(OR MOST RECENT EDITION).

CONCRETE WHEEL-CHAIR RAMPS WITH DETECTABLE WARNING PANEL

NOT TO SCALE



WHEEL-CHAIR RAMP DETAIL

DRAWN BY: CLR	DATE: 2/4/10		SCALE: N/	А
SURVEY BY:		CHECK	ED BY:	
CONTRACT NO.:				SHEET I OF I
REVISIONS				